# Append LF (Line Feed) to Barcode Data

LF (Line Feed) moves the cursor to the next line on a display. It is the same as the 'Enter (₩n)' key for Android system.

You can append the LF to every scan or only to a specific barcode scan.

| to Every Scan            | Use Terminator |
|--------------------------|----------------|
| Only to Specific Barcode | Use PEW        |


### **APPLIES TO**

Point Mobile Android models with scanner

# Set LF as Terminator (Append to Every Scan)

When setting terminator as LF, the LF will be appended to every barcode scan.

- 1. Turn on Go to ScanSettings > Basic.
- 2. Find Terminator, and set as LF.



## Append to Specific Barcode Only

If you want to append LF only to specific barcodes, you can use PEW.

You can access PEW in **EmKit or Settings** > **ScanSettings** > **Wedge**.

1. Turn on Enable extended wedge.

2. Tap Configuration extended wedge.

| Wedge                        |  |
|------------------------------|--|
| On 🌑                         |  |
| Transmit AIM ID              |  |
| Group separator<br>GS        |  |
| Label                        |  |
| Prefix                       |  |
| Suffix                       |  |
| Character set                |  |
| Charset<br>UTF-8             |  |
|                              |  |
| Extended wedge               |  |
| Enable extended wedge        |  |
| Configuration extended wedge |  |

3. Tap a style and choose Condition. And set the condition (Symbologies, Data length, etc.) you want to apply the LF.

| Extended wedge | Condition - Style0 |
|----------------|--------------------|
| On 🦲           | On 🔷               |
| 0: Style0      | Symbologies        |
| Delete         | Symbologies        |
| Rename         | Data length        |
| Condition      | Data length<br>0   |
| Actions        | String position    |
| Up             | String             |
| Down           | Position<br>0      |
|                |                    |
| ADD            |                    |

- 4. Press back button. And tap the style and choose Actions.
- 5. Tap ADD and select Send remaining and tap OK. (Send remaining is for sending the barcode data first.)
- Press back button and tap ADD to add Send char action.
   Set Value as 10.

| (The ASCII code for LF is 10).<br>Action - Style0 |   |  |
|---|---|--|
| Action - Styleo                                   |   |  |
| On  | • |  |
| Action  |   |  |
| Action<br>Send char                               |   |  |
| Order   |   |  |
| Order<br>5  |   |  |
| Value   |   |  |
| Value<br>10                                       |   |  |
|   |   |  |
|   |   |  |
|   |   |  |
|   |   |  |

You can append other terminator characters. Enter the ASCII code as you want. If you want to append TAB + LF, use two Send char actions. One is for TAB (09), and another is for LF (10). Character ASCII Code 09 TAB (Horizontal Tab) 32 Space

Refer to PEW Introduction or ScanSettings - PEW for more information about PEW.

### **RELATED ARTICLES**

- PM60 WEH Missing '0' at the Start of Barcode
  Powerful Extended Wedge, PEW
  PM3 ScanSetting via Demo Application
  Turn On/Off barcode Data Wedge via Intent